



1210 AMERICAN BLVD.
WEST CHESTER, PA 19380
PHONE 800-232-5060

TECHNICAL DATA SHEET

#46 Stainless Steel Open End Pop Rivet



- PRDH304046

***PAINTING AVAILABLE**

SPECIFICATIONS

| | |
|------------------------|-------------------------------------|
| Rivet Size | 1/8" (.122-.128) |
| Hole Size (Drill size) | .129-.133 (#30) |
| Mandrel Diameter nom. | .076 |
| Head Diameter | .250 |
| Head Height | .040 |
| Rivet Length | .525 |
| Grip Range | .313-.375 |
| Finish | Mill Finish |
| Material | Body is 18-8 SS, Mandrel Is 18-8 SS |

CAPACITIES

| | |
|---------------|-----|
| Tensile (Lbs) | 530 |
| Shear (Lbs) | 420 |

CONFORMANCE:

Manufactured per IFI-114 Standards

INSTALLATION:

#30 High Speed Steel Drill Bit Required. Can be installed with battery powered or manual rivet installation tools

DISTRIBUTED BY:

Fastener Systems Inc. 1210 American Blvd., West Chester, PA 19380

Disclaimer: All test results are based on testing done in a laboratory. Specific job conditions should be taken into consideration when specifying the proper fastener. Because applications vary, FSI assumes no liability for the use of this information.