



TECHNICAL DATA SHEET

#8 - 18 PHILLIPS MODIFIED TRUSS 410 STAINLESS STEEL TYPE 2 - SDPW410#08S



SPECIFICATIONS	
Minor thread diameter	0.116 - 0.122"
Major thread diameter	0.161 - 0.166"
Head diameter across flats	0.415 - 0.435"
Material	410 STAINLESS STEEL
Finish	PASSIVATED
Headmark	FSI4

CAPACITIES			LENGTHS AVAILABLE
Drilling application		0.035 - 0.100"	9/16"
Strength (Lbs./Ultimate):			3/4"
Tensile		1,970 lbs.	1/2"
Torque		60 inch / lbs.	1"
			1 1/4"
PULLOUT (Ultimate)			2"
24 ga. to 24 ga.	528 lbs.		
26 ga. to 26 ga.	325 lbs.		

INSTALLATION: *PAINTING AVAILABLE

Install with 2500 rpm screw gun with #2 Phillips Drive. Impact drivers are not recommended.

CONFORMANCE:

Fasteners conform to the SAE J78 and all applicable IFI Standards.

DISTRIBUTED BY:

Fastener Systems Inc. 1210 American Blvd., West Chester, PA 19380

Disclaimer: All test results are based on testing done in a laboratory. Specific job conditions should be taken into consideration when specifying the proper fastener. Because applications vary, FSI assumes no liability for the use of this information.