



TECHNICAL DATA SHEET

#12-11 SQUARE DRIVE PANCAKE HEAD CARBON STEEL TYPE 17



SPECIFICATIONS	
Minor thread diameter	.146154"
Major thread diameter	.208215"
Head diameter across flats	.433472"
Material	SAE 1022 STEEL
Finish	1000 HOUR RUSPERT LONG LIFE COATING
Headmark	FSI

CAPACITIES	LENGTHS AVAILABLE
CAFACITIES	LEING IIIS AVAILABLE

Drilling Capacity		1"
Strength (Lbs. / Ultimate):		1 1/2"
Tensile	2,820 lbs.	2"
Torque	104 in. lbs.	
Shear	2,146 lbs.	
PULLOUT (Ultimate)		

<u> </u>	U	LL(UU	1 (U	lti	ma	ate	9)

5/8" Ply	wood	491 lbs.	
3/4" Ply	wood	584 lbs.	
2x4	Pine	980 lbs	
7/16"	OSB	303 lbs.	
21/32" OSB		383 lbs.	

*PAINTING AVAILABLE

INSTALLATION:

Install with 2500 rpm screw gun with #2 Square Drive. Impact drivers are not recommended.

DISTRIBUTED BY:

Fastener Systems Inc. 1210 American Blvd. West Chester, PA 19380

Disclaimer: All test results are based on testing done in a laboratory. Specific job conditions should be taken into consideration when specifying the proper fastener. Because applications vary, FSI assumes no liability for the use of this information.